

COMPARE ALL ARROW SPRAY GUN MODELS

Attributes	CM 11	CM 11A	CM 16	CM 16A
Product Photo				
Packing Photo				
Fitted With Nozzle Type				

Voltage/Frequency/Watts/Current	110V / 220V AC 50 / 60 Hz 60W/600mA	110V / 220V AC 50 / 60 Hz 60W/600mA	110V / 220V AC 50 / 60 Hz 40W/500mA	110V / 220V AC 50 / 60 Hz 40W/500mA
Insulation	Class 1	Class 1	Class 1	Class 1
Extended Nozzle	No	Yes (Bent at 30 deg)	No	Yes (Bent at 30 deg)
Spray Type	Fixed Straight Line High Velocity Spray	Adjustable from Mist spray to Straight Line High Velocity Spray	Fixed Straight Line High Velocity Spray	Adjustable from Mist spray to Straight Line High Velocity Spray
Pressure Adjustment	Yes	Yes	Yes	Yes
Earthed	Yes	Yes	Yes	Yes
Electric Plug / Wire Length	3 pin / 3 metres	3 pin / 3 metres	3 pin / 3 metres	3 pin / 3 metres
Fuse Protection	Yes - Replaceable Glass Fuse 5x20mm ; 800mA	Yes - Replaceable Glass Fuse 5x20mm ; 800mA	Yes - Replaceable Glass Fuse 5x20mm ; 800mA	Yes - Replaceable Glass Fuse 5x20mm ; 800mA
Body	Mirror Finished Impact Resistant Aluminium	Mirror Finished Impact Resistant Aluminium	Flame Retardant Glass Filled Nylon	Flame Retardant Glass Filled Nylon
Inductor Coil	Flame Retardant Glass Filled Nylon and High Temperature Resistant Copper Wire, Special Electrical Steel	Flame Retardant Glass Filled Nylon and High Temperature Resistant Copper Wire, Special Electrical Steel	Flame Retardant Glass Filled Nylon and High Temperature Resistant Copper Wire, Special Electrical Steel	Flame Retardant Glass Filled Nylon and High Temperature Resistant Copper Wire, Special Electrical Steel

Switch (Press to On / Release to Off)	Flame Retardant Plastic with Copper Contacts	Flame Retardant Plastic with Copper Contacts	Flame Retardant Plastic with Copper Contacts	Flame Retardant Plastic with Copper Contacts
Internal Wiring	Heat Resistant Teflon Coated Wire of 600V Rating	Heat Resistant Teflon Coated Wire of 600V Rating	Heat Resistant Teflon Coated Wire of 600V Rating	Heat Resistant Teflon Coated Wire of 600V Rating
Cylinder Assembly	Special Bronze alloy with Superfinished Piston Bore	Special Bronze alloy with Superfinished Piston Bore	Special Bronze alloy with Superfinished Piston Bore	Special Bronze alloy with Superfinished Piston Bore
Piston	Hardchromed & Superfinished SS	Hardchromed & Superfinished SS	Hardchromed & Superfinished SS	Hardchromed & Superfinished SS
Solvent	As suitable to the application other than Flammable Solvents	As suitable to the application other than Flammable Solvents	As suitable to the application other than Flammable Solvents	As suitable to the application other than Flammable Solvents
Solvent Spill Proof System	Yes	Yes	Yes	Yes
Jar Capacity	850ml	850ml	700ml	700ml
Output per Second (MI)	1.5ml	1.65ml	1.5ml	1.65ml
Output Pressure	2400 psi	2400 psi	1900 psi	1900 psi
Rated Usage / Rest Time	15 Sec On / 30 Sec Off	15 Sec On / 30 Sec Off	15 Sec On / 30 Sec Off	15 Sec On / 30 Sec Off
Pilferproof Shrink Packed	Yes	Yes	Yes	Yes
Package includes	1 Unit Spray Gun, Detailed Booklet, Spares Set	1 Unit Spray Gun, Detailed Booklet, Spares Set	1 Unit Spray Gun, Detailed Booklet, Spares Set	1 Unit Spray Gun, Detailed Booklet, Spares Set
Identification Unique Serial Number	Yes	Yes	Yes	Yes
Security Genuine Product Hologram	Yes	Yes	Yes	Yes
Unit Weight - Dry / With Solvent	1.5 kgs / 2.1 kgs	1.5 kgs / 2.1 kgs	1.2 kgs / 1.7 kgs	1.2 kgs / 1.7 kgs
Unit Weight - One Pc Packed	1.75 kgs	1.79 kgs	1.45 kgs	1.50 kgs
Pcs / Carton	10	10	10	10
Carton Weight	19.5 kgs	20 kgs	16.2 kgs	16.6 kgs
Carton Size	75x27x52cms	75x27x52cms	75x27x52cms	75x27x52cms
Country of Origin	India	India	India	India